



ELECTRIC

AP No.	Description	Qty. Stock
COIL, BLACK MOLDED		
51-1361	110/120V, 50/60HZ, .05A, .518" ID, (New Style). Common on U.S. Ranges	
CONTACTOR		
44-1081	3 Pole, 110/120V, 40A Inductive, 50A Resistive, Hartland	
GENERATORS, PG9 PILOT		
48-1123	Thermopile, 600-750 MV, 36" Wire Leads w/Spade Terminals for 2 Screw Mount	
48-1131	650-750 MV, 31" Coaxial Lead, Coaxial Thermopile Threads = 3/8"-32. For Robertshaw Valves Only	
SWITCHES, INFINITE		
42-1023	120V/15A, (5) 1/4" Tab Terminals	
42-1024	240V/15A, (5) 1/4" Tab Terminals	
SWITCH, INFINITE – KITS		
42-1019	120V/15A, Commercial Duty Infinite Switch Kits, For Screw or Palnut Mount, 2 1/8" Break-Off Stem, Stem Adaptors, and Dial (2" Dia. OFF-LO-2-6-HI, Universal Mount), 5% at Low Setting	
42-1020	240V/15A, Commercial Duty Infinite Switch Kits, For Screw or Palnut Mount, 2 1/8" Break-Off Stem, Stem Adaptors, and Dial (2" Dia. OFF-LO-2-6-HI, Universal Mount), 5% at Low Setting	
THERMOPILES		
51-1357	24", 2 Lead, W/R, w/Spade Terminals for 2 Screws	
51-1121	36", 2 Lead, 250-750 MV	
51-1122	36", Coaxial, 250-750 MV, 3/8"-32 Threads	
51-1346	Armored, 36", with PG9 Adaptor, 750 MV, 2 Lead Wire w/Spade Terminals for 2 Screw Mount	
51-1347	Armored, 70", 2 Lead, 250-650 MV, PG9 Adaptor not included	
THERMOSTATS		
46-1032	S, Temp 175-550, Bulb 3/16" x 11 5/8", Cap 60", Mount 1, includes Knob, Insert & Overlay	
46-1028	SP, has Positive Off, Temp 100-450, Bulb 3/16" x 11 5/8", Cap 60", Mount 1 Vert, 2" Breakaway Stem, includes Knob & Bezel	
46-1152	KX, Temp 100-450, Bulb 3/16" x 11-1/2", Cap 36"	
46-1096	KX, Dip-Sealed, Temp 200-400, Bulb 3/8" x 5 5/8", Cap 36", Mount 1, 1/4" MPT Stuff Box	
48-1006	LCHM Safety with Manual Reset, Temp 450 Fixed, Bulb 1/4" x 4-7/8", Cap 30", 1/4" Nickel Stuff Box	
46-1272	RX, Temp 200-400, Bulb 3/8" x 5", Cap 36", Mount 11, 1/4" MPT Stuff Box	
THERMOSTAT KITS		
46-1534	SP, has Positive Off, Temp 60-250, Bulb 1/4" x 9 1/4", Cap 60", 2" Breakaway Stem, includes Knob & Bezel	

KNOBBS & DIALS

AP No.	Description	Qty. Stock
DIALS		
22-1004	2" Dia., OFF-450-100, Black w/Silver Dial Insert, Mount .187", Position 4 Way	
22-1027	2 1/4" Dia., OFF-400-200, Black w/White Printed No.s, Mount .187", Flat Down	
KNOBBS		
22-1576	Universal Electric Knob Kit: includes (5) Knobs, (10) Inlays & (25) Stem Inserts (5 each Blue, Green, Gray, Red, Yellow)	
22-1075	2" x 1", Black Plastic, Rectangle, Mount .240", Flat Down, Set Screw Down, Oven	
22-1014	Valve Knob, 1 1/4" Dia, OFF-PILOT-ON, Mounts w/Screw. For 700 Series Gas Pilot Safety Valves	
22-1013	Valve Knob, 2 1/8" Dia., Rectangle, Chrome, Mount .240", Set Screw is included	
22-1019	2 1/8" x 1", Black Plastic, Mount .240", Flat Up, Set Screw Down	
22-1112	2" Dia, Chrome, Mount .240", Flat Up and Down, 5/16" Metal Protrusion, No Set Screw	
22-1164	2" Dia, OFF-ON, Chrome, Mount .240", Flat Down, 3/8" Metal Protrusion	
22-1464	2" Dia, OFF-ON, Chrome, Mount .240", Flat Up, 3/8" Metal Protrusion	

GAS

AP No.	Description	Qty. Stock
CONTROL, GAS SAFETY		
54-1011	Nat, 3 1/2" WC, 3/4" FPT In x 3/4" FPT Out, includes 3/4" x 1/2" Reducer	
CONVERSION KITS		
51-1060	LP to Nat, for Lever Acting Regulator	
51-1059	Nat to LP, for Lever Acting Regulator, 6-12" WC	
COVER PLATE		
51-1471	Blank, Used on R/S 700 (Non-Hydraulic) and 710 Series Safety	
GAS COCK		
52-1013	1/8" MPT Out x 3/8" FPT In	
GAS HOSES – JET FORCE		
32-1637	1/2" x 48" L, Yellow Plastic Coated Stainless Steel Corrugated and Braided Gas Hose with Female Swivel Ends, includes (1) Gas Male Flare Fitting and (1) Gas Female Flare Fitting.	
32-1634	3/4" x 48" L, Yellow Plastic Coated Stainless Steel Corrugated and Braided Gas Hose with Female Swivel Ends, includes (1) Gas Male Flare Fitting and (1) Gas Female Flare Fitting.	
GAS HOSE KITS – JET FORCE		
32-1645	1/2" x 48", Yellow Plastic Coated Stainless Steel Corrugated & Braided Gas Hose, Quick Disconnect, Restraining Device, Shut-Off Valve & (2) 90° Elbows	
32-1647	3/4" x 48", Yellow Plastic Coated Stainless Steel Corrugated & Braided Gas Hose, Quick Disconnect, Restraining Device, Shut-Off Valve & (2) 90° Elbows.	
MAGNET HEAD KITS		
51-1106	J Type Pilot, In/Out 1/8" FPT, with Adaptors 1/4" & 3/16" CCT, Screws & Gasket	
51-1107	K Type Pilot, Out 1/8" FPT, with Adaptors 1/4" & 3/16" CCT, Screws & Gasket	



GAS (Cont.)

AP No.	Description	Qty. Stock
ORIFICE KIT		
26-3911	Includes: (4) #56, Hood Orifice, 3/8"-27, (4) #72, Hood Orifice, 3/8"-27, (3) #56, Hood Orifice, 1/2"-27, (3) #72, Hood Orifice, 1/2"-27, (8) #55, 1/8" MPT x 1/8" FPT Orifice, (8) #70, 1/8" MPT x 1/8" FPT Orifice, (4) #56, 7/16"-27 Burner Orifice, (4) #72, 7/16"-27 Burner Orifice, (3) Nat 3/16" Pilot Orifice, (3) LP 3/16" Pilot Orifice, (3) Nat 1/4" Pilot Orifice, (3) LP 1/4" Pilot Orifice, (1) Nat 1/4" CCT Pilot Orifice Elbow, (1) LP 1/4" CCT Pilot Orifice Elbow, (6) Nut 3/16" CCT, (6) Ferrule 3/16" CCT, (6) Nut 1/4" CCT, (6) Ferrule 1/4" CCT	
PILOT HEAD		
51-1036	1/4" CCT w/Nut & Ferrule, Stainless Steel	
PILOT KITS		
51-1108	3/16" & 1/4", Nat/LP, w/Orifices	
51-1474	3/16" & 1/4", Nat/LP, w/Orifices, Flame Pattern Straight	
PILOT TUBE		
51-1475	3/16" x 24", Copper Clad Steel, Bendable, includes Compression Nut & Ferrule	
PRESSURE REGULATORS		
52-1009	Nat Gas, 1/2" FPT, 250,000 BTU, Gas In/Out, 3-6" WC	
52-1011	Nat Gas, 3/4" FPT, 250,000 BTU, Gas In/Out, 3-6" WC, 1/2 PSI	
QUICK DISCONNECT DEVICE		
26-1262	1/2" FPT, Gas Quick Disconnect Assembly	
26-1263	3/4" FPT, Gas Quick Disconnect Assembly	
SWIVELS		
26-2526	1/2" Super Swivel 360° Multi-Plane Fitting, 1/2 PSIG Max	
26-2527	3/4" Super Swivel 360° Multi-Plane Fitting, 1/2 PSIG Max	
THERMOCOUPLES		
51-1426	Baso, Husky, 48" Coaxial Thermocouple, 20-30 MV with Thick Capillary, 11/32"-32 Threads	
51-1428	Baso, Standard, 48" Coaxial Thermocouple, 20-30 MV, 11/32"-32 Threads	
51-1118	Baso, Heavy-Duty, 48" Coaxial Thermocouple, 20-30 MV with Thick Capillary, 11/32"-32 Threads	
51-1110	10 Pack Assortment, includes (1) ea 18", (4) ea 24", (4) ea 36", (1) ea 48", all 20-30 MV	



26-3911



51-1036



51-1108



51-1474



51-1475



52-1009,
52-1011



26-1262



26-1263



26-2526,
26-2527



51-1426



51-1428



51-1118



51-1110

GAS (Cont.)



46-1017

46-1051



46-1037

46-1038



46-1027

46-1211



51-1179



51-1180



52-1666

52-1075



52-1076

52-1008



52-1163

52-1130,
52-1132

54-1026

54-1036

AP No.	Description	Qty. Stock
THERMOSTATS		
46-1017	GS, Temp 200-400, Bulb 3/8" x 5 3/8", Cap 30", Gas In/Out 1/4" F CCT Tube & 1/4" Stuff Box	
THERMOSTAT KITS		
46-1051	FDTH, Temp 300-650, Bulb 3/16" x 14 3/4", Cap 54", Out 3/8 FPT, includes Dial	
46-1037	BJWA, with 3/16" CCT Pilot, Temp 250-550, Bulb 3/16" x 11 5/8", Cap 48", includes Dial, Bezel, Stem Adaptors, Gasket & Screws	
46-1038	BJWA, with 3/16" CCT Pilot, with By-Pass Adj at Top & Gas Inlet Down, Temp 150-550, Bulb 3/16" x 11 5/8", Cap 72", includes Dial, Bezel, Stem Adaptors, Gasket, Screws & Plugs	
46-1027	BJWA, with By-Pass Adj at Top & Gas Inlet Down, Temp 150-400, Bulb 3/16" x 8", Cap 36", includes Dial, Bezel, Stem Adaptors, Gasket & Screws	
46-1211	BJWA, Temp 150-400, Bulb 3/16" x 8", Cap 36", Out 1/4" FPT, Rotation 180 Body Up, No Pilot, Wide Flange, includes Dial, Bezel, Stem Adaptors, Gasket, Screws & Plugs	
TIPS, PILOT		
51-1179	For 1/4" Tubing	
51-1180	For 3/16" Tubing	
VALVES, BURNER		
52-1666	Gas In 1/8" NPT, Gas Out 3/8"-27, comes with #46 Hood Orifice & Point, Adjustable, Stem 1 3/4" Long, Flat Down, On/Off	
52-1075	1/8 MPT x 3/8"-27, comes with #40 Adj Orifice, Rotation Off/On, Stem Position Down, Stem Size .240", Ctr Inlet to End of Stem 2", Angle 90	
52-1076	1/8 MPT x 3/8"-27, comes with #40 Adj Orifice, Rotation Off/On, Stem Position Down, Stem Size .240", Stem 1 3/4" Long, Ctr Inlet to End of Stem 2-1/2", Angle 90	
52-1008	1/8 MPT x 3/8"-27, comes with #42 Adj Orifice, Rotation Off/On, Stem Position Down, Stem Size .240", Ctr Inlet to End of Stem 2 1/8", Angle 90	
52-1163	Top, Gas In 1/8" NPT, Gas Out 3/8"-27, Off/On, comes with #46 Adj Hood Orifice & Point, Brass, Not Push to Turn, Stem 1 3/16" Long, D-Stem 1/4"	
VALVES, GAS SHUT-OFF		
52-1130	1/2" FPT, with Yellow Handle, Dormont	
52-1132	3/4" FPT, with Yellow Handle, Dormont	
VALVES, GAS SOLENOID		
54-1026	3/8" FPT Gas In/Out, Nat/LP, with 1/8" FPT Pilot Out, 120V, 121,000 BTU, NC, Width 2", Robertshaw, .05A. This is new style with Black Molded Coil	
VALVE, PILOT SAFETY		
54-1036	Nat/LP, 3/8" FPT, 1/8" FPT Pilot In/Out, Width 2 7/8", 163,000 BTU, Baso	



85-1039



26-1365



26-1366



85-1114



26-1369,
26-1368



32-1774



72-1185



72-1092



72-1091



26-1374,
26-1375



85-1109



85-1112



26-1419,
26-1418

HARDWARE/MAINTENANCE

AP No.	Description	Qty. Stock
CONNECTORS, PORCELAIN		
85-1039	High-Temp Porcelain Wire Nuts, for (2) #14 GA Wires, 7/8" x 1/2", Medium, 25/Pk	
FITTINGS, BREAK-AWAY		
26-1365	3/16" CCT Breakaway Ferrule, Each, 3/16" Tubing, 24 Thread per inch, Breakaway Nut & Sleeve	
26-1366	1/4" CCT Breakaway Ferrule, Each, 1/4" Tubing, 24 Thread per inch, Breakaway Nut & Sleeve	
GREASE, GAS COCK		
85-1114	2 1/2 Oz. Tube, Temp Range 32-175° F, Boiling Point 450° F	
NUT, COMPRESSION		
26-1369	1/4" CCT, Sold Each	
26-1368	3/16" CCT, Sold Each	
OILER, ZOOM SPOUT		
32-1774	1/4" 4 Fl. Oz., 14" Telescoping Zoom Spout for Hard to Reach Areas	
PUFFER, PILOT		
72-1185	Used to Clean Pilot Assemblies	
REAMERS		
72-1092	Medium, 1/8"	
72-1091	Small, 3/32"	
SLEEVES		
26-1374	3/16" CCT, Brass Ferrule	
26-1375	1/4" CCT, Brass Ferrule	
TAPE		
85-1109	PTFE, 1/2" x 520" Long Roll, White, Seals Pipe and Fittings Threads	
85-1112	PVC All Weather Black Electrical Tape, 3/4" x 60 Ft, 7 Mil, Temps up to 176° F, UL Listed	
TUBE, ALUMINUM		
26-1419	1/4" Dia. OD, 50 Ft Roll, for Nat or LP Gas	
26-1418	3/16" Dia. OD, 50 Ft Roll, for Nat or LP Gas	

DON'T FORGET!

We also offer a large selection of MRO Supplies:

- Bulbs
- Cordsets
- Fuses
- Fuse Holders
- Hi-Temp Terminals
- Hi-Temp Wire
- Silicon Sealant
- Wire Nuts